

RECESSED

Kit for recessed Saniflow hand dryer



KT0005
White finish



KT0005B
Black matte finish



KT0005C
Bright finish



KT0005CS
Satin finish

General description

- Kit for recessed Saniflow hand dryer (hand dryer not included).
- The kit for recessed Saniflow makes the Saniflow hand dryer suitable for the compliance of the ADAAG norm (US) – that limits to 4 inches (100mm) the horizontal projection of the devices installed in bathrooms for public use-, bestowing on that hand dryer the quality of “specific for the disabled”.
- Maximum robustness and vandal-proof.
- Excellent integration and aesthetical level.

Components and materials


- **CABINET:** made of electro-zinc iron, 1.5 mm thick. It includes 4 M5 bolts welded on top of the base plate for fitting the Saniflow hand dryer.
- **FRAME:** 1.5 mm thick, made of steel white finish (KT0005) or black matte (KT005B) or AISI 304 stainless steel bright finish (KT0005C) or satin finish (KT0005CS), with 4 screw holes of Ø 9 mm for mounting on the wall.
- **GASKET:** made of grey rubber, offers a reinforcing outside protection that minimizes vibrations and noise.
- **NUTS AND BOLTS:** for fitting the dryer to the kit and the frame to the wall. It includes: 4 nuts DIN 934 M5, 4 washers DIN 125 M5, 4 stainless steel screws DIN 7981 32 x 5,5 mm and 4 wall plugs F8.

NOTE: nuts and bolts for the mounting of the cabinet to the wall are not included. Use of stainless steel nuts and bolts are recommended.

Technical specifications

Dimensions	345 x 440 x 118 mm
Cabinet thickness	1.5 mm
Frame thickness	1.5 mm

Dimensions



Dimensions: ± 4%

Hand dryer not included